

EXTERIOR PRIMER

Description: **RESISTO EXTERIOR PRIMER** is a solvent-based primer containing synthetic polymers and adhesion-enhancing resins.
It is used to prime and prepare exterior concrete, metal, wood and plywood surfaces to enhance the adherence of **RESISTO** self-adhesive membranes and waterproofing tapes.

Application conditions:

- Minimum application temperature: -10 °C (14 °F).
- Apply to dry, clean surfaces.

Packaging:

- 910 ml (30 oz), 3.78 L (1 US gal) and 18.9 L (5 US gal) containers

Average coverage:

- 0.2 to 0.3 L/m² (0.5 to 0.75 US gal/100 ft²).
1 L (0.25 US gal) will cover 3 to 5 m² (32 to 55 ft²)
- Coverage may vary depending on porosity of the surface.

Properties

Properties	EXTERIOR PRIMER	
Colour	Green	
Specific gravity	0.90 kg/L	7.5 lb/US gal
Solids content	31 %	
Brookfield viscosity, 25 °C (77 °F)	1000 cP	
Flash point, ASTM D93	-3 °C	26.6 °F
Drying time	15 min. to 2 hours, depending on temperature and amount used	

(All values are nominal)

Storage:

- Maximum storage temperature: 40 °C (104 °F).
- Can be stored at temperatures below -10 °C (14 °F).
- Shelf life: 5 years in tightly closed original packaging, stored in a cool, well-ventilated area.

Precautions: **RESISTO EXTERIOR PRIMER** is a high flammable product. Keep it away from direct sunlight and away from open flame. Keep it away from any ignition sources during its use. After installation, keep flames away till solvent fumes have been eliminated. Do not smoke while using it. Harmful if inhaled, swallowed or when in contact with the skin. In closed area, ventilate carefully, forcing the ventilation if necessary and ensure surveillance. Do not pour residues in drains.

The **EXTERIOR PRIMER** could be used with different types of support. Test the **EXTERIOR PRIMER** over a small area to ensure compatibility with the support.

Do not apply **EXTERIOR PRIMER** onto polystyrene surfaces.

For further information, consult the Material Safety Data Sheet.



NOTE: **RESISTO** may modify the composition and/or utilisation of its products without prior notice. Consequently orders will be filled according to the latest specification.