



1675, HAGGERTY
 DRUMMONDVILLE, QC.
 Telephone : (819) 478-8408
 Fax : (819) 478-0199
 Web Site: www.resisto.ca

TECHNICAL DATA SHEET 110414RCAN2E
Cancels & replaces 110112RCAN1E

FOUNDATION COATING

Description : *RESISTOSEAL FOUNDATION COATING* is a bitumen-based, non-fibrated coating used as a damproofing for foundation walls, footings, retaining walls, wing walls, abutments and culverts.

Application : *RESISTOSEAL FOUNDATION COATING* can be applied with a brush or a roller in a continuous film. A sprayable version is also available on request. Surfaces must be dry and free of oil, grease, dirt and loose materials. Concrete surfaces must be sound and free of cracks or other surface irregularities.

Use one of the *RESISTOSEAL* or *RESISTO PLASTIC CEMENTS* to fill irregularities at form ties prior to apply *RESISTOSEAL FOUNDATION COATING*.

Approximate coverage (in the field): 0.5 to 0.7 L/m² (1.2 to 1.7 gal US/100 ft²)

Limitation : *RESISTOSEAL FOUNDATION COATING* must be dry when you touch it before backfilling.

At low temperature, product must be conditioned at a temperature above 10 °C prior its use.

Do not apply product over damp or frost-covered substrates.

Properties: *RESISTOSEAL FOUNDATION COATING* meets performance criteria of CGSB 37-GP-6MA.

Properties	<i>FOUNDATION COATING</i>	
Colour	Black	
Specific gravity at 20 °C (68 °F)	1 kg/L	8.3 lb/US gal
Solids by weight	77 %	
Maximum application temperature range	35 °C	95 °F
Service temperature range	up to 70 °C	Up to 158 °F
Brookfield Viscosity at 25 °C	4500 cP	
Drying time	12 to 24 hours depending on temperature and quantity applied	

(All values are nominal)

Packaging: 3.78L (1 gal US) & 18.9 L (5 gal US) pails.
 Shelf life: Up to 12 months in original sealed containers, protected from humidity.

Cleaning: Tools can be cleaned with petroleum solvents such as mineral spirits, xylene, etc.

Precautions: *RESISTOSEAL FOUNDATION COATING* is a flammable product. Store in a cool, dry area. Use in a well ventilated area, far away from any open flame. Harmful if inhaled, swallowed or when in contact with skin.

CONSULT THE MATERIAL SAFETY DATA SHEET PRIOR TO USE.

NOTE : *RESISTO* may modify the composition and/or utilisation of its products without prior notice. Consequently orders will be filled according to the latest specification.