



1675, HAGGERTY  
 DRUMMONDVILLE, QC.  
 Telephone : (819) 478-8408  
 Fax : (819) 478-0199  
 Web Site: [www.resisto.ca](http://www.resisto.ca)

<b>TECHNICAL DATA SHEET</b> <b>110414RCAN3E</b>
Cancels & replaces 110117RCAN1E

## WINTER GRADE FOUNDATION COATING

**Description :** The **RESISTOSEAL WINTER GRADE FOUNDATION COATING** is a bitumen-based, non-fibrated coating used as a damproofing for foundation walls, footings, retaining walls, wing walls, abutments and culverts. It is especially designed for application at lower temperature.

**Application :** The **WINTER GRADE FOUNDATION COATING** can be applied with a brush, a roller or could be sprayed in a continuous film.  
 Surfaces must be dry and free of oil, grease, dirt and loose materials. Concrete surfaces must be sound and free of cracks or other surface irregularities.  
 Use **RESISTOSEAL** or **RESISTO PLASTIC CEMENT** to fill irregularities at form ties prior to apply **RESISTOSEAL WINTER GRADE FOUNDATION COATING**.  
 Approximate coverage (in the field): 0.5 to 0.7 L/m<sup>2</sup> (1.2 to 1.7 gal US/100 ft<sup>2</sup>)

**Limitation :** The **RESISTOSEAL WINTER GRADE FOUNDATION COATING** must be dry when you touch it before backfilling.  
 Product should be conditioned at a temperature above 10 °C about 24 hours prior its use.  
 Do not apply over damp or frost-covered substrates.

**Properties:** The **RESISTOSEAL WINTER GRADE FOUNDATION COATING** meets performance criteria of CGSB 37-GP-6MA.

Properties	<b>WINTER GRADE FOUNDATION COATING</b>	
Colour	Black	
Specific gravity at 20 °C (68 °F)	1 kg/L	8.3 lb/US gal
Solids by weight	70 %	
Maximum application temperature range	35 °C	95 °F
Service temperature range	up to 70 °C	Up to 158 °F
Brookfield Viscosity at 25 °C	1000 cP	
Drying time	12 to 36 hours depending on temperature and quantity applied	

(All values are nominal)

**Packaging:** 3.78L (1 gal US) & 18.9 L (5 gal US) pails.  
 Shelf life: Up to 12 months in original sealed containers, protected from humidity.

**Cleaning:** Tools can be cleaned with petroleum solvents such as mineral spirits, xylene, etc.

**Precautions:** **RESISTOSEAL FOUNDATION COATING is a flammable product.** Store in a cool, dry area. Use in a well ventilated area, far away from any open flame. Harmful if inhaled, swallowed or when in contact with skin.

**CONSULT THE MATERIAL SAFETY DATA SHEET PRIOR TO USE.**

**NOTE :** RESISTO may modify the composition and/or utilisation of its products without prior notice. Consequently orders will be filled according to the latest specification.