

**DURAL FAST SET EPOXY LV (1:1) PART B**

Version 3.

Print Date 06/30/2010

REVISION DATE: 05/07/2010

SECTION 1 - PRODUCT IDENTIFICATION / PREPARATION INFORMATION**Product Information**

Trade name : DURAL FAST SET EPOXY LV (1:1) PART B
Product code : B5324

Supplier : Euclid Canada
2835 Grande-Allée
St-Hubert, QC J4T 2R4
Telephone : 1-800-667-0920
Emergency Phone: : (613) 996-6666

Product use : Curative

Preparation Information

Prepared by: : Sewnauth Raghunandan
Date: : 05/07/2010
Telephone : (416) 421-3300

SECTION 2 - HAZARDS IDENTIFICATION**Emergency Overview**

Amber. Liquid. May cause slight irritation to the respiratory system. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel.

Acute Potential Health Effects/ Routes of Entry

Inhalation : May cause slight irritation to the respiratory system.
Eyes : Vapors or liquid may cause tearing, blurred vision, severe irritation, and possible chemical burns.
Ingestion : May cause gastrointestinal irritation, nausea, and vomiting. May cause chemical burns to stomach, mouth, nose, and throat.
Skin : May cause itching, reddening, inflammation. May cause severe burns, blistering and skin damage. May cause sensitization resulting in irritation, itching and redness. May cause a rash.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

May cause sensitization by contact. Prolonged skin contact may cause irritation, burns or dermatitis. Repeated overexposure to vapors and/or material may injure the liver, kidneys and respiratory system unless suitable engineering controls and/or personal protective equipment are used. May aggravate persons sensitized to amines. Prolonged or repeated contact/exposure to aromatic petroleum distillates may cause defatting, drying, and irritation of the skin, dermatitis, and central nervous system (CNS) effects. Prolonged or repeated exposure to epoxy resin can cause irritation to skin, eyes, skin sensitization, temporary eye injury. Certain epoxy resins are reported to be mutagenic in some laboratory tests. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

**DURAL FAST SET EPOXY LV (1:1) PART B**

Version 3.

Print Date 06/30/2010

REVISION DATE: 05/07/2010

SECTION 3 : HAZARDOUS INGREDIENTS

Chemical Name	CAS-No.	Weight % Range
Bisphenol A	80-05-7	15.0 - 40.0
Heavy aromatic naphtha	64742-94-5	15.0 - 40.0
Epichlorohydrin polymer	25085-99-8	10.0 - 30.0

The ingredients listed above are hazardous as defined in the controlled products regulation. (CPR).

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

Inhalation : Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel.

Eye contact : Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.

Skin contact : Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.

Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

SECTION 5: FIRE / EXPLOSION HAZARDS

Flash point : 205 °F, 96 °C

Method : Not available.

Lower explosion limit : Not available.

Upper explosion limit : Not available.

Autoignition temperature : Not available.

Extinguishing media : If water fog is ineffective, use carbon dioxide, dry chemical or foam.

Hazardous combustion products : Carbon monoxide and carbon dioxide can form. Smoke, fumes. Nitrogen oxides can form.

Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).

Fire and explosion conditions : Product may ignite if heated in excess of its flash point. Vapors may travel to sources of ignition and flashback. Vapor concentrations in enclosed areas may ignite explosively. Empty containers may contain ignitable vapors.

SECTION 6 - SPILLS / LEAKS / ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Remove sources of ignition immediately. Stop flow of material if safe to do so. Contain spill and keep out of water courses. Ventilate area.

**DURAL FAST SET EPOXY LV (1:1) PART B**

Version 3.

Print Date 06/30/2010

REVISION DATE: 05/07/2010

SECTION 7 - HANDLING AND STORAGE

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Do not smoke, weld, generate sparks, or use flame near container. Do not use in confined or poorly ventilated areas. Personal protective equipment must be worn during maintenance or repair of contaminated mixer, reactor, or other equipment. Store under dry warehouse conditions away from heat and all ignition sources.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**Personal protection equipment**

- Respiratory protection** : Wear NIOSH/MSHA approved vapor respirator with appropriate cartridge when the vapor concentration is expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
- Hand protection** : Use suitable impervious nitrile or neoprene gloves and protective apparel to reduce exposure.
- Eye protection** : Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
- Skin and body protection** : Prevent contact with shoes and clothing. Use rubber apron and overshoes.
- Protective measures** : Inspect and replace equipment at regular intervals. Use professional judgment in the selection, care, and use.
- Engineering measures** : Use only in well ventilated areas. Provide maximum ventilation in enclosed areas. Use local exhaust when the general ventilation is inadequate.

Exposure Limits

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Regulation</u>	<u>Limit</u>	<u>Form</u>
Bisphenol A	80-05-7			

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

- Physical State** : Liquid
- Form** : Liquid
- Color** : Amber
- Odor** : Amine
- pH** : Not available.
- Vapour pressure** : Not available.
- Vapor density** : Heavier than air
- Melting point/range** : Not available.
- Freezing point** : Not available.
- Boiling point/range** : Not available.
- Water solubility** : Negligible
- Evaporation Rate:** : Not available.

**DURAL FAST SET EPOXY LV (1:1) PART B**

Version 3.

Print Date 06/30/2010

REVISION DATE: 05/07/2010

Specific Gravity : 1.031

% Volatile Weight : 20 %

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid : Oxidizing agents.Epoxies.Isocyanates.Acids.

Stability : Material is stable under normal storage, handling, and use.

Hazardous polymerization : Will not occur under normal conditions.

SECTION 11 - TOXICOLOGICAL INFORMATION

Bisphenol A, CAS-No.: 80-05-7

Acute oral toxicity (LD-50 oral)

4,100 mg/kg (Rat) 3,300 mg/kg (Rat) 5,280 mg/kg (Mouse)
4,100 mg/kg (Mouse) 2,500 mg/kg (Mouse)**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

SECTION 13 - WASTE DISPOSAL CONSIDERATIONS

Disposal Method : Dispose as hazardous waste according to all local, state, federal and provincial regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATA**TDG / DOT Shipping Description:**

UN1760, CORROSIVE LIQUID, N.O.S. (Alkaline Amine), 8, PG III

SECTION 15 - REGULATORY INFORMATION**North American Inventories:**

All components are listed or exempt from the TSCA inventory.

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

Canadian Regulations:

WHMIS Classification : D2A, D2B, E

This is a "controlled product" under the Canadian Workplace Hazardous Materials Information System (WHMIS).

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

Other Regulations:

When appropriately mixed with the other part, product has a VOC less water and exempt solvent of:

0 g/l



DURAL FAST SET EPOXY LV (1:1) PART B

Version 3.
REVISION DATE: 05/07/2010

Print Date 06/30/2010

SECTION 16 - OTHER INFORMATION

HMIS Rating :

Health	2
Flammability	1
Reactivity	1
PPE	

0 = Minimum
1 = Slight
2 = Moderate
3 = Serious
4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Sewnauth Raghunandan

Legend

- ACGIH - American Conference of Governmental Hygienists
- DOT - Department of Transportation
- DSL - Domestic Substance List
- EPA - Environmental Protection Agency
- HMIS - Hazardous Materials Information System
- IARC - International Agency for Research on Cancer
- MSHA - Mine Safety Health Administration
- NDSL - Non-Domestic Substance List
- NIOSH - National Institute for Occupational Safety and Health
- NTP - National Toxicology Program
- OSHA - Occupational Safety and Health Administration
- PEL - Permissible Exposure Limit
- RCRA - Resource Conservation and Recovery Act
- STEL - Short Term Exposure Limit
- TLV - Threshold Limit Value
- TSCA - Toxic Substances Control Act
- TWA - Time Weighted Average
- V - Volume
- VOC - Volatile Organic Compound
- WHMIS - Workplace Hazardous Materials Information System